



IPC-4 comm Universal Control Switcher

Introduction

Comm Universal Control Switcher is a user friendly wired panel that control by RS 232 which can be program by customer on side and selectable baud rate, power delay on time, power delay off time. The Switchers is more convenient for customer to install and change projector whenever they need.

Features

- **Universal protocol**
Self program baud rate, protocol
- **One touch selection**
LED back lit including sound buzzer
- **Electronic Volume Control**
Able to increase or decrease digital volume
- **Signal Amplifier**
250 MHz
- **Software**
Optional

Technical Specification

- **Power Supply:**
DC 12V power adapter
- **Input:**
 - PC 1 Signal - VGA (D Sub 15 pin female)
 - PC 1 Audio - 3.5mm mini jack
 - PC 2 Signal - VGA (D Sub 15 pin female)
 - PC 2 Audio - 3.5mm mini jack

- Component Y,C,B - RCA connector
- S-Video - S-Video socket
- Video Signal - RCA connector
- Audio Signal - RCA connector

- **Output:**

- PC Signal - VGA (D Sub 15 pin female) (250MHz)
- PC Signal - Soldering
- Video Signal - Soldering
- Audio Signal - Soldering 2 pairs (Front & Rear)
- RS 232 - Soldering 2 pairs

- **Selector Switch:**

- Projector On
- Projector Off
- Blank On/Off (toggle button)
- Sync On/Off (toggle button)
- Volume Up (digital)
- Volume Down (digital)
- VGA Selector (toggle button PC 1 or PC 2 with LED indicator)
- Video Selector (toggle button S-Video or Video with LED indicator)
- All the buttons with buzzer